



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

ब्यांगडाडा, भापा,
२०७३
(सूचना प्रविधि शाखा)
शिवसताक्षी नगरपालिकाको कार्यालय
ब्यांगडाडा, भापा,
कोशी प्रदेश, नेपाल
२०७३

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

कोशी प्रदेश, नेपाल ।

प.सं. : ०५०१०९
च.नं. : ८२४६

मिति: २०८१/०३/१०

श्री सबै फर्म तथा संस्थाहरु ।

बिषय:- दरभाउ उपलब्ध गराउने सम्बन्धमा ।

उपरोक्त बिषयमा यस शिवसताक्षी नगरपालिकालाई विपतका तत्काल उल्लेखित सामग्रीहरु खरिद गर्नुपर्ने भएको हुदाँ पत्र मितिले ४ दिन भित्र निम्न सामग्रीहरुको दरभाउ उपलब्ध गराईदिनु हुन सार्वजनिक सूचना प्रकाशन गरिएको व्यहोरा अनुरोध छ ।

निम्न:-

S.N	Item	Qty	Rate	Amount	Remark
1	24 Port Main Switch	2			
2	24 Port Secondary Switch	3			
3	8 Port Switch	1			
4	Server Power Supply Unit	1			
5	PDU	1			
6	SMPS	1			
7	Switch Rack	1			
8	Cat6 Cable	1			Cartoon
9	IP Phone	5			
	Total				
	VAT				
	Grand Total				

नोट:- उल्लेखित सामग्रीहरुको Specification यसै सूचनाको साथमा संलग्न गरिएको व्यहोरा अनुरोध छ ।

7/10/21
गणेश अधिकारी
सूचना प्रविधि अधिकृत



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

कोशी प्रदेश, नेपाल।

ब्यांगडड भन्ना
०२३-४७०३२३
(सूचना प्रविधि शाखा)
नगर कार्यपालिकाको कार्यालय
ब्यांगडड, नेपाल
२०७३
Specification

S.N	Item	Specification	Remark
1	24 Port Main Switch	10/100/1000Base-T ports: 24 SEP Ports: 4 PoE/PoE+ Ports: 24 Max PoE budget: 370W Layer Type: Layer 3 Switching Capacity: 56 Gbps Forwarding Rate: 42 Mpps Mac Address Table: 16000 Maximun VLAN Support: 4094 Port Surge: 6kv Flow Control: Yes STP (IEEE 802.1d): Yes RSTP (IEEE 802.1w): Yes MSTP (IEEE 802.1s): Yes Port Fast: Yes ACL Entries: 1900 Flash Memory: 256 MB Power Supply: 110-240V AC, 6A FAN: 2 Acoustic Noise: <45dB Power Supply: Power Cord Warranty: 2years on part	
2	24 Port Support Switch	10/100/1000Base-T ports: 24 SEP Ports: 2 PoE/PoE+ Ports: 24 Max PoE budget: 370W Switching Capacity: 52 Gbps Forwarding Rate: 38.69 Mpps Mac Address Table: 8000 Maximun VLAN Support: 16 Port Surge: 4kv Flow Control: Yes STP (IEEE 802.1d): No RSTP (IEEE 802.1w): No MSTP (IEEE 802.1s): No Port Fast: Yes ACL Entries: 1200 Power Supply: 110-240V AC, 6A FAN: Inbuilt 1 Acoustic Noise: <45dB	

शिवसताक्षी नगर कार्यपालिका
सूचना प्रविधि शाखा
अधिकृत



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

नवलपरासी, नेपाल
नगर कार्यपालिकाको कार्यालय
(सूचना प्रविधि शाखा)
कोशी प्रदेश, नेपाल
२०७३

कोशी प्रदेश, नेपाल ।

		Power Supply: Power Cord Warranty: 2years on part	
3	8 Port Switch	Ports: 9 x 10/100/1000Base-T, 8 x PoE+ ports Switching capacity: 18 Gbps MAC address table: 4000 Fan: Fanless MTBF: > 200,000 PoE: 120W, IEEE 802.3at / IEEE 802.3af Forwarding rate: 13.39 Mpps Maximum VLAN: 16 Port surge: 4 kV Warranty: 2years on part	
4	Server Power Supply Unit	PART NUMBER: D750E-S6 WATTAGE: 750W INPUT RANGE: 100-240V 10-5A 50-60HZ OUTPUT RANGE: +12.2V - 61.47A +12VSB - 3.0A CERTIFICATION: 80 PLUS PLATINUM HOT PLUG / NOT HOT PLUG: HOT PLUG COMPATIBILITY: POWEREDGE R530 / R540 / R630 / R640 / R730 / R730XD / R740 / R740XD / R830 / R930 / R7415 / ADDITIONAL INFORMATION: 94% EFFICIENCY EXTENDED POWER PERFORMANCE EPP	
5	Power Distribution Unit (PDU)	Connectors:20+4 Pin Type: Enterprise UPS Compatible Model: Universal 19" standard equipment Features: Rack Mountable Color: Any Maximun Power: 2000W MPN: PDU Voltage: 110V	
6	SMPS	No. of Channels: 8 Channel Ouput Voltage: 12V Rated Power (Watts): 60W Current: 5A Load Regulation: 5% Ouput Current: 10Amp Color: Any	
7	Switch Rack	Color: Any Mountign Dimensions: 19" x 6U x 269 mm Demensions: 600 x 368 x 600[+/-2mm] Type Cabinets: wall mount fully assembled-two section Material: Cold-rolled steel SPCC, 1.2mm, 1.5mm, RAL9004(black), metallic Warranty: 1Year	

7/10/23
अधिकारी



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

ब्यांगडाडा, काभ्रे
शिवसताक्षी नगरपालिका कार्यालय
सूचना प्रविधि शाखा
काभ्रे, नेपाल

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

कोशी प्रदेश, नेपाल ।

8	Cat6 Cable	<p>Conductor: Stranded Bare Copper (x 32 AWG) Insulation: HDPE (CMI-75E) Nominal Wall Thickness: 0.178mm, Min. Thickness: 0.153mm Color Code: Pair 1: Blue & White/Blue Pair 2: Orange & White/Orange Pair 3: Green & White/Green Pair 4: Brown & White/Brown Jacket (Grey): 75°C LSZH Compound Nominal Wall Thickness: 0.585mm Min. Thickness: 0.458mm Overall Diameter: 5.8mm ± 0.3mm Conductor Resistance: 14.00Ω/100m 20o Max.</p>	
2	Ip Phone	<p>4 SIP accounts 2.8-inch 320*240 color display Support EHS wireless headset Support IPv4 , IPv6 protocol Dual Gigabit ports, integrated PoE Support local 6-way audio conference HD audio on speakerphone and handset with G.722 and Opus Newly increased phone book/ voice message key, 2 line keys with LED light Support G.723.1, G.726 narrow-band voice codec</p>	

7/11/23
[Signature]
नगर अधिकारी
सूचना प्रविधि अधिकृत